

Report No.:

Test Time: 2025-09-16 15:27

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: 24D

Luminous Width (mm): -14

Current: 0.132 A

Power Factor: 0.964

Luminous Length (mm): -575

Voltage: 230.7 V

Power: 29.40 W

Photometric Results

CIE Class: Direct

Measurement Flux: 2817.1 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H27.3

Vertical Diffuse Angle(50%): V27.3

Luminaire Efficacy Rating (LER): 95.87

Max. Intensity: 13242.59 cd

S/MH(C0/C180): 0.47

Total Rated Lamp Lumens: 2817.1 lm

Efficiency: 100%

Upward Ratio: 0%

Central Intensity: 12911.16 cd


Pos of Max. Intensity: H0 V4

S/MH(C90/C270): 0.47

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0



Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 13243 cd

(10%): 1324 cd	(16%): 2119 cd
(25%): 3311 cd	(40%): 5297 cd
(63%): 8343 cd	(100%): 13243 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 131.6 lx

(1%): 1.3 lx	(2%): 2.6 lx
(5%): 6.6 lx	(10%): 13.2 lx
(20%): 26.3 lx	(50%): 65.8 lx
(100%): 131.6 lx	


C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 12911.2 lx
— (1%): 129.1 lx — (2%): 258.2 lx
— (5%): 645.6 lx — (10%): 1291.1 lx
— (20%): 2582.2 lx — (50%): 6455.6 lx
— (100%): 12911.2 lx

C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

The Average Illuminance Effective Figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	11.5	12.0	11.7	12.2	12.4	11.4	11.9	11.6	12.1	12.3
3H	13.6	14.2	13.9	14.4	14.6	13.5	14.0	13.7	14.2	14.4
4H	14.7	15.2	15.0	15.5	15.7	14.4	14.9	14.7	15.2	15.4
6H	15.1	15.5	15.4	15.8	16.1	14.7	15.2	15.0	15.4	15.7
8H	15.0	15.5	15.4	15.8	16.1	14.7	15.1	15.0	15.4	15.7
12H	15.0	15.4	15.3	15.7	16.0	14.6	15.1	15.0	15.4	15.7
X=4H Y=2H	12.1	12.6	12.4	12.9	13.1	12.0	12.5	12.3	12.8	13.0
3H	14.6	15.1	15.0	15.4	15.7	14.5	14.9	14.8	15.2	15.5
4H	15.8	16.2	16.2	16.5	16.9	15.6	16.0	15.9	16.3	16.6
6H	16.2	16.5	16.6	16.9	17.3	15.8	16.2	16.2	16.6	16.9
8H	16.1	16.5	16.5	16.8	17.2	15.8	16.1	16.2	16.5	16.9
12H	16.1	16.4	16.5	16.8	17.2	15.7	16.0	16.2	16.4	16.9
X=8H Y=4H	16.1	16.5	16.6	16.8	17.2	15.9	16.2	16.3	16.6	17.0
6H	16.5	16.7	16.9	17.2	17.6	16.2	16.4	16.6	16.9	17.3
8H	16.4	16.7	16.9	17.1	17.6	16.1	16.4	16.6	16.8	17.3
12H	16.4	16.6	16.9	17.0	17.5	16.1	16.3	16.6	16.7	17.2
X=12H Y=4H	16.1	16.4	16.5	16.8	17.2	15.9	16.2	16.3	16.6	17.0
6H	16.4	16.7	16.9	17.1	17.6	16.1	16.4	16.6	16.8	17.3
8H	16.4	16.6	16.9	17.1	17.6	16.1	16.3	16.6	16.8	17.2
Variations with the observer position at spacings:										
S=1.0H	+0.4/-0.4					+0.4/-0.5				
S=1.5H	+0.8/-0.7					+0.8/-0.6				
S=2.0H	+1.2/-0.7					+1.3/-0.7				

Calculate in accordance with CIE Pub.117. The table is revised with 2817lm ($8\log(F/F_0) = 3.6$).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	1480	52.5
	FL (0°-30°)	1394	49.5
	FM (30°-60°)	66	2.3
	FH (60°-80°)	20	0.7
	FVH (80°-90°)	0	0.0
	BACK LIGHT	1337	47.5
	BL (0°-30°)	1254	44.5
	BM (30°-60°)	64	2.3
	BH (60°-80°)	19	0.7
	BVH (80°-90°)	0	0.0
	UP LIGHT	0	0.0
	UL (90°-100°)	0	0.0
	UH (100°-180°)	0	0.0
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B3 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B3 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	12904.8	12.3	12.3	0.44	0.44
1.0-2.0	12883.8	37.0	49.3	1.31	1.75
2.0-3.0	12844.8	61.4	110.8	2.18	3.93
3.0-4.0	12778.8	85.5	196.3	3.04	6.97
4.0-5.0	12660.8	108.9	305.3	3.87	10.84
5.0-6.0	12471.3	131.1	436.3	4.65	15.49
6.0-7.0	12186.5	151.3	587.6	5.37	20.86
7.0-8.0	11781.8	168.6	756.3	5.99	26.85
8.0-9.0	11246.0	182.3	938.5	6.47	33.32
9.0-10.0	10575.8	191.4	1130.0	6.79	40.11
10.0-11.0	9767.3	195.2	1325.1	6.93	47.04
11.0-12.0	8837.6	193.2	1518.4	6.86	53.90
12.0-13.0	7818.1	185.6	1703.9	6.59	60.49
13.0-14.0	6744.5	172.7	1876.6	6.13	66.62
14.0-15.0	5662.5	155.5	2032.1	5.52	72.13
15.0-16.0	4614.9	135.2	2167.3	4.80	76.93
16.0-17.0	3645.9	113.6	2280.9	4.03	80.97
17.0-18.0	2793.5	92.1	2373.0	3.27	84.24
18.0-19.0	2077.3	72.3	2445.3	2.57	86.80
19.0-20.0	1498.4	54.8	2500.1	1.95	88.75
20.0-21.0	1053.6	40.5	2540.6	1.44	90.19
21.0-22.0	729.9	29.3	2569.9	1.04	91.23
22.0-23.0	502.0	21.1	2591.0	0.75	91.97
23.0-24.0	345.8	15.1	2606.1	0.54	92.51
24.0-25.0	244.7	11.1	2617.2	0.40	92.91
25.0-26.0	180.5	8.5	2625.7	0.30	93.21
26.0-27.0	139.4	6.8	2632.6	0.24	93.45
27.0-28.0	114.1	5.8	2638.3	0.21	93.66
28.0-29.0	100.1	5.2	2643.6	0.19	93.84
29.0-30.0	92.7	5.0	2648.6	0.18	94.02
30.0-31.0	89.5	5.0	2653.6	0.18	94.20
31.0-32.0	88.1	5.0	2658.6	0.18	94.38
32.0-33.0	87.1	5.1	2663.7	0.18	94.56
33.0-34.0	87.1	5.3	2669.0	0.19	94.74
34.0-35.0	86.0	5.3	2674.4	0.19	94.93
35.0-36.0	86.4	5.5	2679.9	0.20	95.13

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	88.1	5.7	2685.6	0.20	95.33
37.0-38.0	88.5	5.9	2691.5	0.21	95.54
38.0-39.0	87.8	6.0	2697.5	0.21	95.76
39.0-40.0	85.7	6.0	2703.5	0.21	95.97
40.0-41.0	83.2	5.9	2709.4	0.21	96.18
41.0-42.0	81.4	5.9	2715.3	0.21	96.39
42.0-43.0	79.3	5.9	2721.2	0.21	96.60
43.0-44.0	75.8	5.7	2726.9	0.20	96.80
44.0-45.0	71.6	5.5	2732.4	0.20	97.00
45.0-46.0	67.1	5.2	2737.7	0.19	97.18
46.0-47.0	62.1	4.9	2742.6	0.18	97.36
47.0-48.0	56.9	4.6	2747.2	0.16	97.52
48.0-49.0	50.9	4.2	2751.4	0.15	97.67
49.0-50.0	45.3	3.8	2755.2	0.13	97.80
50.0-51.0	40.7	3.4	2758.6	0.12	97.93
51.0-52.0	35.1	3.0	2761.6	0.11	98.03
52.0-53.0	29.8	2.6	2764.2	0.09	98.12
53.0-54.0	26.0	2.3	2766.5	0.08	98.21
54.0-55.0	22.8	2.0	2768.5	0.07	98.28
55.0-56.0	21.1	1.9	2770.5	0.07	98.35
56.0-57.0	20.0	1.8	2772.3	0.06	98.41
57.0-58.0	19.3	1.8	2774.1	0.06	98.47
58.0-59.0	20.0	1.9	2775.9	0.07	98.54
59.0-60.0	21.1	2.0	2777.9	0.07	98.61
60.0-61.0	21.1	2.0	2779.9	0.07	98.68
61.0-62.0	21.8	2.1	2782.0	0.07	98.76
62.0-63.0	22.5	2.2	2784.2	0.08	98.83
63.0-64.0	23.2	2.3	2786.5	0.08	98.92
64.0-65.0	23.9	2.4	2788.9	0.08	99.00
65.0-66.0	23.9	2.4	2791.2	0.08	99.08
66.0-67.0	23.9	2.4	2793.6	0.09	99.17
67.0-68.0	23.9	2.4	2796.1	0.09	99.25
68.0-69.0	23.9	2.4	2798.5	0.09	99.34
69.0-70.0	23.5	2.4	2800.9	0.09	99.43
70.0-71.0	22.5	2.3	2803.2	0.08	99.51
71.0-72.0	21.8	2.3	2805.5	0.08	99.59

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	12911.2	12911.2								
G1.0	13039.0	12758.1								
G2.0	13141.5	12596.6								
G3.0	13213.1	12428.1								
G4.0	13242.6	12231.5								
G5.0	13175.2	11994.2								
G6.0	13022.1	11693.6								
G7.0	12745.5	11285.0								
G8.0	12335.4	10761.2								
G9.0	11765.3	10122.2								
G10.0	11047.7	9368.1								
G11.0	10165.8	8487.6								
G12.0	9172.9	7524.3								
G13.0	8093.0	6482.3								
G14.0	6968.1	5434.6								
G15.0	5840.5	4406.7								
G16.0	4749.4	3463.0								
G17.0	3750.9	2620.4								
G18.0	2885.8	1916.9								
G19.0	2151.4	1355.2								
G20.0	1558.8	928.2								
G21.0	1103.8	623.5								
G22.0	768.2	424.1								
G23.0	525.2	290.7								
G24.0	360.9	206.4								
G25.0	254.2	157.3								
G26.0	184.0	126.4								
G27.0	140.4	106.7								
G28.0	115.2	94.1								
G29.0	101.1	89.9								
G30.0	92.7	87.1								
G31.0	89.9	88.5								
G32.0	88.5	85.7								
G33.0	88.5	85.7								
G34.0	88.5	85.7								
G35.0	85.7	84.3								
G36.0	88.5	87.1								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	88.5	88.5								
G38.0	88.5	88.5								
G39.0	88.5	85.7								
G40.0	85.7	82.8								
G41.0	82.8	81.4								
G42.0	82.8	78.6								
G43.0	78.6	77.2								
G44.0	75.8	71.6								
G45.0	71.6	67.4								
G46.0	67.4	61.8								
G47.0	63.2	56.2								
G48.0	57.6	50.5								
G49.0	50.5	44.9								
G50.0	46.3	39.3								
G51.0	42.1	35.1								
G52.0	33.7	29.5								
G53.0	30.9	25.3								
G54.0	25.3	22.5								
G55.0	22.5	21.1								
G56.0	21.1	19.7								
G57.0	21.1	18.3								
G58.0	19.7	18.3								
G59.0	21.1	21.1								
G60.0	21.1	21.1								
G61.0	21.1	21.1								
G62.0	22.5	22.5								
G63.0	22.5	22.5								
G64.0	25.3	22.5								
G65.0	25.3	22.5								
G66.0	25.3	22.5								
G67.0	25.3	22.5								
G68.0	25.3	22.5								
G69.0	25.3	22.5								
G70.0	25.3	21.1								
G71.0	22.5	21.1								
G72.0	22.5	21.1								
G73.0	21.1	19.7								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

