

Report No.:

Test Time: 2025-08-26 20:54

## Luminaire Property

Luminaire Manufacturer:

Lamp Description: V8E F90 930

Luminous Width (mm): -46

Current: 0.101 A

Power Factor: 0.630

Luminous Length (mm): -46

Voltage: 232.0 V

Power: 14.90 W

## Photometric Results

CIE Class: Direct

Measurement Flux: 1396.4 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H41.3

Vertical Diffuse Angle(50%): V41.3

Luminaire Efficacy Rating (LER): 93.77

Max. Intensity: 3166.15 cd

S/MH(C0/C180): 0.72

Total Rated Lamp Lumens: 1396.4 lm

Efficiency: 100%

Upward Ratio: 0%

Central Intensity: 2902.12 cd


Pos of Max. Intensity: H0 V11

S/MH(C90/C270): 0.72

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0



Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:


## Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:


## Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

## Isocandela (rectangle)



Imax (100%): 3166 cd

( 10%): 317 cd	( 16%): 507 cd
( 25%): 792 cd	( 40%): 1266 cd
( 63%): 1995 cd	(100%): 3166 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

## IsoLux Plot



Mounting Height: 10.0m    Max Lux(100%): 30.4 lx

( 1%): 0.3 lx	( 2%): 0.6 lx
( 5%): 1.5 lx	( 10%): 3.0 lx
( 20%): 6.1 lx	( 50%): 15.2 lx
(100%): 30.4 lx	

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

## Illuminance at a Distance



C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

## Vertical IsoLux Plot



Lowest(m): 1.0m    Highest(m): 11.0m    Max Lux: 3036.8 lx  
— ( 1%): 30.4 lx                      — ( 2%): 60.7 lx  
— ( 5%): 151.8 lx                      — ( 10%): 303.7 lx  
— ( 20%): 607.4 lx                      — ( 50%): 1518.4 lx  
— (100%): 3036.8 lx


C Plane (°): 0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°): 0.0-90.0: 1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## The Average Illuminance Effective Figure



C Plane (°): 0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°): 0.0-90.0: 1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

## UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	13.6	14.3	13.8	14.5	14.7	12.8	13.5	13.1	13.7	13.9
3H	13.5	14.1	13.7	14.3	14.5	12.7	13.3	13.0	13.5	13.8
4H	13.4	14.0	13.7	14.2	14.5	12.6	13.2	12.9	13.4	13.7
6H	13.3	13.8	13.6	14.1	14.4	12.5	13.1	12.9	13.4	13.6
8H	13.3	13.8	13.6	14.1	14.4	12.5	13.0	12.8	13.3	13.6
12H	13.2	13.7	13.6	14.0	14.3	12.5	13.0	12.8	13.3	13.6
X=4H Y=2H	13.4	14.0	13.7	14.2	14.5	12.6	13.2	12.9	13.5	13.7
3H	13.2	13.7	13.6	14.0	14.3	12.5	13.0	12.8	13.3	13.6
4H	13.1	13.6	13.5	13.9	14.3	12.4	12.8	12.8	13.2	13.5
6H	13.1	13.5	13.5	13.8	14.2	12.3	12.7	12.7	13.1	13.4
8H	13.0	13.4	13.4	13.8	14.2	12.3	12.6	12.7	13.0	13.4
12H	13.0	13.3	13.4	13.7	14.1	12.2	12.5	12.6	12.9	13.4
X=8H Y=4H	13.0	13.4	13.4	13.8	14.2	12.3	12.6	12.7	13.0	13.4
6H	12.9	13.2	13.4	13.6	14.1	12.2	12.4	12.6	12.9	13.3
8H	12.9	13.1	13.3	13.6	14.0	12.1	12.4	12.6	12.8	13.3
12H	12.8	13.0	13.3	13.5	14.0	12.1	12.3	12.5	12.7	13.2
X=12H Y=4H	13.0	13.3	13.4	13.7	14.1	12.2	12.5	12.6	12.9	13.4
6H	12.9	13.1	13.3	13.6	14.0	12.1	12.4	12.6	12.8	13.3
8H	12.8	13.0	13.3	13.5	14.0	12.1	12.3	12.5	12.7	13.2
Variations with the observer position at spacings:										
S=1.0H	+5.4/-11.5					+5.1/-11.6				
S=1.5H	+8.2/-20.9					+7.9/-21.0				
S=2.0H	+10.2/-23.9					+9.9/-24.6				

Calculate in accordance with CIE Pub.117. The table is revised with  $1396\text{lm}$  ( $8\log(F/F_0) = 1.2$ ).

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

**FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM**

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	747	53.5
	FL ( 0°-30°)	704	50.4
	FM (30°-60°)	43	3.1
	FH (60°-80°)	0	0.0
	FVH (80°-90°)	0	0.0
	BACK LIGHT	650	46.5
	BL ( 0°-30°)	614	43.9
	BM (30°-60°)	36	2.6
	BH (60°-80°)	0	0.0
	BVH (80°-90°)	0	0.0
	UP LIGHT	0	0.0
	UL (90°-100°)	0	0.0
	UH (100°-180°)	0	0.0
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B2 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B2 U0 G0

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

## Zonal Lumen

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	2901.4	2.8	2.8	0.20	0.20
1.0-2.0	2899.3	8.3	11.1	0.60	0.79
2.0-3.0	2896.9	13.9	25.0	0.99	1.79
3.0-4.0	2896.3	19.4	44.3	1.39	3.18
4.0-5.0	2899.8	24.9	69.3	1.79	4.96
5.0-6.0	2905.5	30.5	99.8	2.19	7.15
6.0-7.0	2910.5	36.1	136.0	2.59	9.74
7.0-8.0	2913.6	41.7	177.7	2.99	12.72
8.0-9.0	2912.5	47.2	224.9	3.38	16.10
9.0-10.0	2905.9	52.6	277.5	3.77	19.87
10.0-11.0	2890.7	57.8	335.2	4.14	24.01
11.0-12.0	2860.3	62.5	397.8	4.48	28.48
12.0-13.0	2812.2	66.7	464.5	4.78	33.26
13.0-14.0	2745.7	70.3	534.8	5.03	38.30
14.0-15.0	2656.3	72.9	607.7	5.22	43.52
15.0-16.0	2539.6	74.4	682.2	5.33	48.85
16.0-17.0	2392.4	74.5	756.7	5.34	54.19
17.0-18.0	2216.9	73.1	829.8	5.23	59.42
18.0-19.0	2017.2	70.2	900.0	5.03	64.45
19.0-20.0	1800.5	65.9	965.9	4.72	69.17
20.0-21.0	1579.2	60.6	1026.5	4.34	73.51
21.0-22.0	1362.4	54.8	1081.3	3.92	77.43
22.0-23.0	1155.1	48.5	1129.8	3.47	80.90
23.0-24.0	967.1	42.3	1172.1	3.03	83.93
24.0-25.0	801.0	36.4	1208.5	2.61	86.54
25.0-26.0	654.2	30.9	1239.4	2.21	88.75
26.0-27.0	526.6	25.8	1265.1	1.85	90.60
27.0-28.0	417.2	21.1	1286.3	1.51	92.11
28.0-29.0	327.1	17.1	1303.4	1.23	93.34
29.0-30.0	255.5	13.8	1317.2	0.99	94.32
30.0-31.0	199.9	11.1	1328.3	0.80	95.12
31.0-32.0	158.1	9.1	1337.3	0.65	95.77
32.0-33.0	127.9	7.5	1344.9	0.54	96.31
33.0-34.0	106.3	6.4	1351.3	0.46	96.77
34.0-35.0	89.6	5.6	1356.9	0.40	97.17
35.0-36.0	76.1	4.8	1361.7	0.35	97.51

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

## Zonal Lumen (Continue 1)

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	65.3	4.3	1366.0	0.31	97.82
37.0-38.0	56.3	3.8	1369.8	0.27	98.09
38.0-39.0	48.7	3.3	1373.1	0.24	98.33
39.0-40.0	42.3	3.0	1376.0	0.21	98.54
40.0-41.0	37.0	2.6	1378.7	0.19	98.73
41.0-42.0	32.5	2.4	1381.0	0.17	98.90
42.0-43.0	28.4	2.1	1383.1	0.15	99.05
43.0-44.0	24.8	1.9	1385.0	0.13	99.18
44.0-45.0	21.6	1.7	1386.7	0.12	99.30
45.0-46.0	18.7	1.5	1388.1	0.10	99.40
46.0-47.0	16.2	1.3	1389.4	0.09	99.50
47.0-48.0	14.1	1.1	1390.6	0.08	99.58
48.0-49.0	12.4	1.0	1391.6	0.07	99.65
49.0-50.0	10.8	0.9	1392.5	0.06	99.72
50.0-51.0	9.1	0.8	1393.3	0.06	99.77
51.0-52.0	7.6	0.7	1393.9	0.05	99.82
52.0-53.0	6.0	0.5	1394.4	0.04	99.86
53.0-54.0	4.8	0.4	1394.8	0.03	99.89
54.0-55.0	3.7	0.3	1395.2	0.02	99.91
55.0-56.0	3.0	0.3	1395.4	0.02	99.93
56.0-57.0	2.3	0.2	1395.7	0.02	99.94
57.0-58.0	1.6	0.2	1395.8	0.01	99.96
58.0-59.0	1.3	0.1	1395.9	0.01	99.96
59.0-60.0	0.9	0.1	1396.0	0.01	99.97
60.0-61.0	0.7	0.1	1396.1	0.00	99.97
61.0-62.0	0.6	0.1	1396.1	0.00	99.98
62.0-63.0	0.5	0.1	1396.2	0.00	99.98
63.0-64.0	0.4	0.0	1396.2	0.00	99.99
64.0-65.0	0.4	0.0	1396.3	0.00	99.99
65.0-66.0	0.4	0.0	1396.3	0.00	99.99
66.0-67.0	0.3	0.0	1396.4	0.00	99.99
67.0-68.0	0.2	0.0	1396.4	0.00	100.00
68.0-69.0	0.1	0.0	1396.4	0.00	100.00
69.0-70.0	0.1	0.0	1396.4	0.00	100.00
70.0-71.0	0.2	0.0	1396.4	0.00	100.00
71.0-72.0	0.1	0.0	1396.4	0.00	100.00

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:

## Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	2902.1	2902.1								
G1.0	2924.6	2876.8								
G2.0	2951.1	2844.8								
G3.0	2974.4	2817.4								
G4.0	2999.9	2793.7								
G5.0	3031.8	2773.9								
G6.0	3063.2	2753.2								
G7.0	3096.9	2728.7								
G8.0	3126.0	2702.6								
G9.0	3148.5	2672.8								
G10.0	3164.9	2637.3								
G11.0	3166.1	2594.5								
G12.0	3140.8	2539.9								
G13.0	3100.4	2467.6								
G14.0	3039.6	2375.0								
G15.0	2951.5	2259.2								
G16.0	2829.1	2118.4								
G17.0	2665.4	1956.9								
G18.0	2471.7	1773.6								
G19.0	2245.8	1577.8								
G20.0	1996.3	1382.1								
G21.0	1743.2	1195.3								
G22.0	1493.6	1017.5								
G23.0	1257.8	851.4								
G24.0	1052.6	706.8								
G25.0	869.2	575.6								
G26.0	709.5	462.6								
G27.0	569.2	365.0								
G28.0	450.6	284.0								
G29.0	354.0	219.8								
G30.0	277.0	171.0								
G31.0	218.2	133.4								
G32.0	173.0	107.7								
G33.0	140.0	91.0								
G34.0	115.9	78.2								
G35.0	97.2	67.0								
G36.0	82.2	58.2								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

## Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	70.2	50.6								
G38.0	60.3	44.2								
G39.0	51.7	38.7								
G40.0	44.8	34.1								
G41.0	39.0	30.2								
G42.0	33.8	26.9								
G43.0	29.5	23.5								
G44.0	25.7	20.6								
G45.0	22.4	17.6								
G46.0	19.4	15.4								
G47.0	16.8	13.3								
G48.0	14.5	11.9								
G49.0	13.1	10.2								
G50.0	11.2	8.5								
G51.0	9.6	7.1								
G52.0	7.8	5.7								
G53.0	6.3	4.3								
G54.0	5.0	3.4								
G55.0	3.9	2.5								
G56.0	3.4	2.1								
G57.0	2.5	1.3								
G58.0	1.8	1.0								
G59.0	1.4	0.8								
G60.0	1.0	0.6								
G61.0	0.7	0.6								
G62.0	0.7	0.6								
G63.0	0.6	0.3								
G64.0	0.4	0.3								
G65.0	0.6	0.3								
G66.0	0.6	0.3								
G67.0	0.3	0.3								
G68.0	0.3	0.0								
G69.0	0.3	0.0								
G70.0	0.3	0.0								
G71.0	0.3	0.3								
G72.0	0.0	0.0								
G73.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



