

**ORBI**

RECESSED DOWNLIGHT





Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

ORBI

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
sandy white
sandy black

BEAM ANGLE ORBI 35 L0
spot 28°
medium 35°
flood 38°
wide flood 53°

BEAM ANGLE ORBI 35 L2
spot 28°
medium 35°
flood 38°
wide flood 53°

BEAM ANGLE ORBI 35 L4
spot 28°
medium 35°
flood 38°
wide flood 53°



ORBI 35 L0

CRI >90


COB

IP20

DALI

≤19 UGR

35



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4W 12V 250MA	3000K	301lm	55.03525
	4000K	316lm	



ORBI 35 L2

CRI >90


COB

IP20

DALI

≤19 UGR

75x35



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4WX2 12V 250MA	3000K	2X301lm	55.03526
	4000K	2X316lm	



ORBI 35 L4

CRI >90


COB

IP20

DALI

≤19 UGR

155x35



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4WX4 12V 250MA	3000K	4X301lm	55.03527
	4000K	4X316lm	