


Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

VOLI

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
sandy white
sandy black

BEAM ANGLE VOLI 75
spot 19°
medium 29°
flood 40°
wide flood 50°

BEAM ANGLE VOLI 95
spot 25°
medium 31°
flood 42°
wide flood 49°



VOLI 75

CRI
>90


COB

350°
23°

IP20

DALI

≤19
UGR



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1123lm	52.07531
	4000K	1179lm	



VOLI 95

CRI
>90


COB

350°
23°

IP20

DALI

≤19
UGR



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
25W 36V 600MA	3000K	2900lm	52.09535
	4000K	3045lm	