Report No.:

Test Time: 2026-09-10 17:36

Luminaire Property

Luminaire Manufacturer:
Luminaire Description: 52.09541 15D
Luminous Width (mm): -82
Current: 0.182 A
Power Factor: 0.962

Luminous Length (mm): -82
Voltage: 233.5 V
Power: 40.90 W

Photometric Results

CIE Class: Direct
Measurement Flux: 4167.9 lm
Downward Ratio: 100%
Horizontal Diffuse Angle(50%): H22.1
Vertical Diffuse Angle(50%): V22.1
Luminaire Efficacy Rating (LER): 101.96
Max. Intensity: 21349.9 cd
S/MH(C0/C180): 0.38

Total Rated Lamp Lumens: 4167.9 lm
Efficiency: 100%
Upward Ratio: 0%

Central Intensity: 21285.06 cd
Pos of Max. Intensity: H0 V1
S/MH(C90/C270): 0.38

Picture Of Luminaire

Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve





C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 21350 cd

(10%): 2135 cd
(16%): 3416 cd
(25%): 5337 cd
(40%): 8540 cd
(63%): 13450 cd
(100%): 21350 cd

C Plane (°):0.0-180.0: 180.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab:
Test Device: CHL-6E
Test Type: TYPE C
Distance: 3.010 m
Temperature:
Humidity:
Operator:
Inspector:

IsoLux Plot



Mounting Height: 10.0m Max Lux(100%): 213.4 lx

(1%): 2.1 lx
(2%): 4.3 lx
(5%): 10.7 lx
(10%): 21.3 lx
(20%): 42.7 lx
(50%): 106.7 lx
(100%): 213.4 lx

C Plane (°):0.0-180.0: 180.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab:
Test Device: CHL-6E
Test Type: TYPE C
Distance: 3.010 m
Temperature:
Humidity:
Operator:
Inspector:

Illuminance at a Distance



Dist(m)	Enadir(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
0.5	85140.24	0.20/0.20	0.0	41632.89
1.0	21285.06	0.39/0.39	0.1	10408.22
1.5	9460.03	0.59/0.59	0.3	4625.88
2.0	5321.27	0.78/0.79	0.5	2602.06
2.5	3405.61	0.98/0.98	0.8	1665.32
3.0	2365.01	1.17/1.18	1.1	1156.47
4.0	1330.32	1.56/1.57	1.9	650.51
5.0	851.40	1.95/1.96	3.0	416.33
15.0	94.60	5.86/5.89	27.0	46.26
20.0	53.21	7.81/7.86	48.0	26.02

Beam Angle(B): H22.1 V22.2 Field Angle(F): H43.1 V43.3

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 21285.1 lx

(1%): 212.9 lx
(2%): 425.7 lx
(5%):1064.3 lx
(10%):2128.5 lx
(20%):4257.0 lx
(50%):10642.5 lx
(100%):21285.1 lx

C Plane (°):0.0-180.0: 180.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab:
Test Device: CHL-6E
Test Type: TYPE C
Distance: 3.010 m
Temperature:
Humidity:
Operator:
Inspector:

中山雅大光电有限公司
www.artdon.cn
0760-22211886
0760-22211890

Area Flux Table

Unit: lm

Vertical plane	-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
-90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-70	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.6	0.0	
-60	0.0	0.0	0.0	0.0	0.1	0.1	0.2	0.3	0.5	0.5	0.4	0.3	0.2	0.1	0.0	0.0	0.0	0.0	2.6	0.0	
-50	0.0	0.0	0.0	0.0	0.1	0.3	0.9	1.7	2.3	2.4	1.9	1.1	0.5	0.2	0.1	0.0	0.0	0.0	11.6	0.0	
-40	0.0	0.0	0.0	0.1	0.3	1.2	2.9	5.1	7.2	7.3	5.5	3.2	1.5	0.4	0.1	0.0	0.0	0.0	34.8	0.0	
-30	0.0	0.0	0.0	0.1	0.7	2.5	6.5	17.0	34.1	35.8	19.4	7.6	3.0	1.0	0.2	0.0	0.0	0.0	128.1	13.8	
-20	0.0	0.0	0.0	0.2	1.1	4.1	15.1	68.3	171.2	181.7	81.5	19.3	5.0	1.6	0.3	0.1	0.0	0.0	549.4	461.2	
-10	0.0	0.0	0.0	0.2	1.4	5.2	26.8	151.9	447.0	484.0	191.8	37.5	6.8	2.0	0.3	0.1	0.0	0.0	1355.0	1285.3	
0	0.0	0.0	0.0	0.2	1.4	5.2	26.8	151.9	447.0	484.0	191.8	37.5	6.8	2.0	0.3	0.1	0.0	0.0	1355.0	1285.3	
10	0.0	0.0	0.0	0.2	1.1	4.1	15.1	68.3	171.2	181.7	81.5	19.3	5.0	1.6	0.3	0.1	0.0	0.0	549.4	461.2	
20	0.0	0.0	0.0	0.1	0.7	2.5	6.5	17.0	34.1	35.8	19.4	7.6	3.0	1.0	0.2	0.0	0.0	0.0	128.1	13.8	
30	0.0	0.0	0.0	0.1	0.3	1.2	2.9	5.1	7.2	7.3	5.5	3.2	1.5	0.4	0.1	0.0	0.0	0.0	34.8	0.0	
40	0.0	0.0	0.0	0.0	0.1	0.3	0.9	1.7	2.3	2.4	1.9	1.1	0.5	0.2	0.1	0.0	0.0	0.0	11.6	0.0	
50	0.0	0.0	0.0	0.0	0.1	0.1	0.2	0.3	0.5	0.5	0.4	0.3	0.2	0.1	0.0	0.0	0.0	0.0	2.6	0.0	
60	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.6	0.0	
70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
Flux(T)	0.0	0.0	0.2	1.3	7.4	27.1	105.1	489.0	1324.6	1423.5	601.1	138.2	34.0	10.4	2.0	0.4	0.0	0.0	4164		
Flux(E)	0.0	0.0	0.0	0.0	0.0	0.0	2.5	390.8	1246.7	1347.2	511.1	22.3	0.0	0.0	0.0	0.0	0.0	0.0		3521	

Horizontal plane

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

The Average Illuminance Effective Figure

Flux Out: 1834.08lm



Height	Avg./Nadir. E	Beam Angle:22.1°	Diameter / Area
1.0m	15323.16/ 21285.06lx		0.39m / 0.12sq.m
1.5m	6810.29/ 9460.03lx		0.59m / 0.27sq.m
2.0m	3830.79/ 5321.27lx		0.78m / 0.48sq.m
2.5m	2451.71/ 3405.61lx		0.98m / 0.75sq.m
3.0m	1702.57/ 2365.01lx		1.17m / 1.08sq.m
3.5m	1250.87/ 1737.56lx		1.37m / 1.47sq.m
4.0m	957.70/ 1330.32lx		1.56m / 1.92sq.m
4.5m	756.70/ 1051.11lx		1.76m / 2.42sq.m
5.0m	612.93/ 851.40lx		1.95m / 2.99sq.m
5.5m	506.55/ 703.64lx		2.15m / 3.62sq.m

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	13.2	13.8	13.4	13.9	14.1	12.6	13.2	12.8	13.4	13.5
3H	13.0	13.6	13.3	13.8	14.0	12.5	13.0	12.7	13.2	13.5
4H	13.0	13.5	13.3	13.7	14.0	12.4	12.9	12.7	13.1	13.4
6H	12.9	13.4	13.2	13.6	13.9	12.3	12.8	12.6	13.1	13.3
8H	12.9	13.3	13.2	13.6	13.9	12.3	12.7	12.6	13.0	13.3
12H	12.8	13.3	13.2	13.6	13.9	12.2	12.7	12.6	13.0	13.3
X=4H Y=2H	13.0	13.5	13.3	13.7	14.0	12.4	12.9	12.7	13.2	13.4
3H	12.8	13.3	13.2	13.6	13.9	12.3	12.7	12.6	13.0	13.3
4H	12.8	13.2	13.1	13.5	13.8	12.2	12.6	12.6	12.9	13.3
6H	12.7	13.0	13.1	13.4	13.8	12.1	12.4	12.5	12.8	13.2
8H	12.6	12.9	13.0	13.3	13.7	12.0	12.4	12.5	12.8	13.2
12H	12.6	12.9	13.0	13.3	13.7	12.0	12.3	12.4	12.7	13.1
X=8H Y=4H	12.6	12.9	13.0	13.3	13.7	12.0	12.4	12.5	12.8	13.2
6H	12.5	12.8	13.0	13.2	13.7	11.9	12.2	12.4	12.6	13.1
8H	12.5	12.7	12.9	13.1	13.6	11.9	12.1	12.4	12.6	13.0
12H	12.4	12.6	12.9	13.1	13.6	11.8	12.0	12.3	12.5	13.0
X=12H Y=4H	12.6	12.9	13.0	13.3	13.7	12.0	12.3	12.4	12.7	13.1
6H	12.5	12.7	12.9	13.1	13.6	11.9	12.1	12.4	12.6	13.0
8H	12.4	12.6	12.9	13.1	13.6	11.8	12.0	12.3	12.5	13.0
Variations with the observer position at spacings:										
S=1.0H	+4.0/-9.1					+3.9/-9.2				
S=1.5H	+6.7/-11.2					+6.6/-11.9				
S=2.0H	+8.7/-18.5					+8.6/-19.1				

Calculate in accordance with CIE Pub.117. The table is revised with 4168lm (8log(F/F0) = 5.0).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	2211	53.1
FL (0°-30°)	2086	50.0
FM (30°-60°)	124	3.0
FH (60°-80°)	2	0.1
FVH (80°-90°)	0	0.0
BACK LIGHT	1957	46.9
BL (0°-30°)	1849	44.4
BM (30°-60°)	106	2.5
BH (60°-80°)	2	0.0
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B3 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B3 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	21255.7	20.3	20.3	0.49	0.49
1.0-2.0	21129.4	60.7	81.0	1.46	1.94
2.0-3.0	20838.0	99.7	180.7	2.39	4.33
3.0-4.0	20338.3	136.2	316.8	3.27	7.60
4.0-5.0	19593.5	168.6	485.4	4.04	11.65
5.0-6.0	18593.1	195.4	680.8	4.69	16.33
6.0-7.0	17365.9	215.6	896.4	5.17	21.51
7.0-8.0	15966.1	228.5	1124.9	5.48	26.99
8.0-9.0	14469.3	234.5	1359.5	5.63	32.62
9.0-10.0	12961.7	234.6	1594.1	5.63	38.25
10.0-11.0	11504.5	229.9	1824.0	5.52	43.76
11.0-12.0	10145.8	221.8	2045.8	5.32	49.08
12.0-13.0	8919.3	211.7	2257.5	5.08	54.16
13.0-14.0	7819.4	200.2	2457.7	4.80	58.97
14.0-15.0	6832.3	187.6	2645.3	4.50	63.47
15.0-16.0	5942.8	174.2	2819.4	4.18	67.65
16.0-17.0	5130.9	159.8	2979.2	3.83	71.48
17.0-18.0	4391.8	144.8	3124.0	3.47	74.95
18.0-19.0	3730.3	129.8	3253.8	3.11	78.07
19.0-20.0	3140.8	115.0	3368.8	2.76	80.83
20.0-21.0	2624.1	100.8	3469.6	2.42	83.24
21.0-22.0	2179.7	87.6	3557.2	2.10	85.35
22.0-23.0	1800.9	75.6	3632.8	1.81	87.16
23.0-24.0	1483.5	64.9	3697.6	1.56	88.72
24.0-25.0	1224.2	55.7	3753.3	1.34	90.05
25.0-26.0	1012.4	47.8	3801.1	1.15	91.20
26.0-27.0	838.6	41.0	3842.1	0.98	92.18
27.0-28.0	698.8	35.4	3877.5	0.85	93.03
28.0-29.0	586.1	30.7	3908.2	0.74	93.77
29.0-30.0	495.3	26.7	3934.9	0.64	94.41
30.0-31.0	422.9	23.5	3958.5	0.56	94.97
31.0-32.0	364.8	20.9	3979.4	0.50	95.48
32.0-33.0	317.4	18.7	3998.1	0.45	95.92
33.0-34.0	277.8	16.8	4014.9	0.40	96.33
34.0-35.0	246.1	15.3	4030.2	0.37	96.70
35.0-36.0	220.1	14.0	4044.2	0.34	97.03

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	196.7	12.8	4057.0	0.31	97.34
37.0-38.0	175.6	11.7	4068.8	0.28	97.62
38.0-39.0	157.6	10.8	4079.5	0.26	97.88
39.0-40.0	141.3	9.9	4089.4	0.24	98.12
40.0-41.0	126.6	9.0	4098.4	0.22	98.33
41.0-42.0	114.2	8.3	4106.7	0.20	98.53
42.0-43.0	102.1	7.6	4114.3	0.18	98.71
43.0-44.0	91.6	6.9	4121.2	0.17	98.88
44.0-45.0	82.2	6.3	4127.5	0.15	99.03
45.0-46.0	72.4	5.7	4133.1	0.14	99.17
46.0-47.0	63.7	5.1	4138.2	0.12	99.29
47.0-48.0	54.7	4.4	4142.6	0.11	99.39
48.0-49.0	47.9	3.9	4146.6	0.09	99.49
49.0-50.0	41.5	3.5	4150.0	0.08	99.57
50.0-51.0	33.2	2.8	4152.8	0.07	99.64
51.0-52.0	26.4	2.3	4155.1	0.05	99.69
52.0-53.0	21.1	1.8	4156.9	0.04	99.74
53.0-54.0	17.3	1.5	4158.5	0.04	99.77
54.0-55.0	14.3	1.3	4159.7	0.03	99.80
55.0-56.0	11.3	1.0	4160.8	0.02	99.83
56.0-57.0	9.4	0.9	4161.6	0.02	99.85
57.0-58.0	9.0	0.8	4162.5	0.02	99.87
58.0-59.0	8.3	0.8	4163.2	0.02	99.89
59.0-60.0	8.3	0.8	4164.0	0.02	99.91
60.0-61.0	7.5	0.7	4164.7	0.02	99.92
61.0-62.0	6.0	0.6	4165.3	0.01	99.94
62.0-63.0	6.0	0.6	4165.9	0.01	99.95
63.0-64.0	6.0	0.6	4166.5	0.01	99.97
64.0-65.0	4.5	0.4	4166.9	0.01	99.98
65.0-66.0	3.4	0.3	4167.3	0.01	99.98
66.0-67.0	2.6	0.3	4167.5	0.01	99.99
67.0-68.0	1.5	0.2	4167.7	0.00	99.99
68.0-69.0	1.5	0.2	4167.9	0.00	100.00
69.0-70.0	0.8	0.1	4167.9	0.00	100.00
70.0-71.0	0.0	0.0	4167.9	0.00	100.00
71.0-72.0	0.0	0.0	4167.9	0.00	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	0.0	0.0	4167.9	0.00	100.00
73.0-74.0	0.0	0.0	4167.9	0.00	100.00
74.0-75.0	0.0	0.0	4167.9	0.00	100.00
75.0-76.0	0.0	0.0	4167.9	0.00	100.00
76.0-77.0	0.0	0.0	4167.9	0.00	100.00
77.0-78.0	0.0	0.0	4167.9	0.00	100.00
78.0-79.0	0.0	0.0	4167.9	0.00	100.00
79.0-80.0	0.0	0.0	4167.9	0.00	100.00
80.0-81.0	0.0	0.0	4167.9	0.00	100.00
81.0-82.0	0.0	0.0	4167.9	0.00	100.00
82.0-83.0	0.0	0.0	4167.9	0.00	100.00
83.0-84.0	0.0	0.0	4167.9	0.00	100.00
84.0-85.0	0.0	0.0	4167.9	0.00	100.00
85.0-86.0	0.0	0.0	4167.9	0.00	100.00
86.0-87.0	0.0	0.0	4167.9	0.00	100.00
87.0-88.0	0.0	0.0	4167.9	0.00	100.00
88.0-89.0	0.0	0.0	4167.9	0.00	100.00
89.0-90.0	0.0	0.0	4167.9	0.00	100.00

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	21285.1	21285.1								
G1.0	21349.9	21102.6								
G2.0	21301.6	20763.4								
G3.0	21102.6	20184.5								
G4.0	20698.6	19367.3								
G5.0	20066.9	18241.1								
G6.0	19204.5	16860.1								
G7.0	18090.3	15308.7								
G8.0	16747.0	13718.1								
G9.0	15256.0	12156.2								
G10.0	13712.1	10722.4								
G11.0	12174.3	9409.3								
G12.0	10743.5	8255.9								
G13.0	9457.5	7220.1								
G14.0	8302.7	6297.5								
G15.0	7275.9	5453.2								
G16.0	6347.2	4694.8								
G17.0	5481.8	3999.8								
G18.0	4706.9	3378.6								
G19.0	4004.3	2831.4								
G20.0	3371.1	2356.5								
G21.0	2819.3	1949.4								
G22.0	2344.4	1605.7								
G23.0	1937.3	1316.2								
G24.0	1598.1	1082.5								
G25.0	1323.7	892.5								
G26.0	1094.6	738.8								
G27.0	906.1	615.1								
G28.0	755.3	518.6								
G29.0	631.7	438.7								
G30.0	532.2	378.4								
G31.0	455.3	325.6								
G32.0	390.5	288.0								
G33.0	337.7	253.3								
G34.0	295.5	224.6								
G35.0	263.8	200.5								
G36.0	235.2	180.9								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	206.6	164.3								
G38.0	186.9	144.7								
G39.0	167.4	131.2								
G40.0	150.8	116.1								
G41.0	135.7	104.0								
G42.0	123.6	93.5								
G43.0	110.1	81.4								
G44.0	102.5	72.4								
G45.0	88.9	64.8								
G46.0	81.4	54.3								
G47.0	72.4	46.7								
G48.0	60.3	39.2								
G49.0	55.8	36.2								
G50.0	48.2	25.6								
G51.0	39.2	19.6								
G52.0	31.7	15.1								
G53.0	25.6	12.1								
G54.0	21.1	10.6								
G55.0	15.1	10.6								
G56.0	12.1	7.5								
G57.0	10.6	7.5								
G58.0	10.6	7.5								
G59.0	7.5	7.5								
G60.0	10.6	7.5								
G61.0	7.5	4.5								
G62.0	7.5	4.5								
G63.0	7.5	4.5								
G64.0	7.5	4.5								
G65.0	4.5	1.5								
G66.0	4.5	3.0								
G67.0	1.5	1.5								
G68.0	3.0	0.0								
G69.0	3.0	0.0								
G70.0	0.0	0.0								
G71.0	0.0	0.0								
G72.0	0.0	0.0								
G73.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table (Continue 2)

Unit: cd

G\C	C0.0	C180.0								
G74.0	0.0	0.0								
G75.0	0.0	0.0								
G76.0	0.0	0.0								
G77.0	0.0	0.0								
G78.0	0.0	0.0								
G79.0	0.0	0.0								
G80.0	0.0	0.0								
G81.0	0.0	0.0								
G82.0	0.0	0.0								
G83.0	0.0	0.0								
G84.0	0.0	0.0								
G85.0	0.0	0.0								
G86.0	0.0	0.0								
G87.0	0.0	0.0								
G88.0	0.0	0.0								
G89.0	0.0	0.0								
G90.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector: