

Report No.:

Test Time: 2026-09-30 19:17

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: 32.10112 24D

Luminous Length (mm): -60

Voltage: 230.7 V

Power: 20.00 W

Lamp Description: BLX V10C 3000K

Luminous Width (mm): -60

Current: 0.092 A

Power Factor: 0.939

Photometric Results

CIE Class: Direct

Measurement Flux: 2150.5 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H26.7

Vertical Diffuse Angle(50%): V26.7

Luminaire Efficacy Rating (LER): 107.57

Max. Intensity: 4360.82 cd

S/MH(C0/C180): 0.45

Total Rated Lamp Lumens: 2150.5 lm

Efficiency: 100%


Upward Ratio: 0%

Central Intensity: 4353.01 cd


Pos of Max. Intensity: H0 V1

S/MH(C90/C270): 0.45

Picture Of Luminaire



Luminous Intensity Distribution Curve



Unit: cd

— C0-C180 — C90-C270

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve




C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



Isocandela (rectangle)



Imax (100%): 4361 cd

(10%): 436 cd	(16%): 698 cd
(25%): 1090 cd	(40%): 1744 cd
(63%): 2747 cd	(100%): 4361 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 43.6 lx

(1%): 0.4 lx	(2%): 0.9 lx
(5%): 2.2 lx	(10%): 4.4 lx
(20%): 8.7 lx	(50%): 21.8 lx
(100%): 43.6 lx	


C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 4353.0 lx
— (1%): 43.5 lx — (2%): 87.1 lx
— (5%): 217.7 lx — (10%): 435.3 lx
— (20%): 870.6 lx — (50%): 2176.5 lx
— (100%): 4353.0 lx

C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

The Average Illuminance Effective Figure



UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	27.0	28.0	27.3	28.3	28.5	26.9	27.9	27.1	28.1	28.3
3H	28.2	29.2	28.6	29.4	29.7	28.0	29.0	28.3	29.2	29.5
4H	28.8	29.6	29.1	29.9	30.2	28.5	29.4	28.9	29.7	29.9
6H	29.2	30.0	29.5	30.3	30.6	28.9	29.7	29.3	30.0	30.3
8H	29.4	30.1	29.7	30.4	30.8	29.1	29.9	29.4	30.2	30.5
12H	29.5	30.2	29.9	30.6	30.9	29.2	29.9	29.6	30.3	30.6
X=4H Y=2H	27.5	28.4	27.8	28.6	28.9	27.4	28.2	27.7	28.5	28.8
3H	28.9	29.7	29.3	30.0	30.3	28.8	29.5	29.1	29.8	30.2
4H	29.6	30.3	30.0	30.6	31.0	29.4	30.1	29.8	30.4	30.8
6H	30.2	30.7	30.6	31.1	31.5	29.9	30.5	30.3	30.9	31.3
8H	30.4	30.9	30.8	31.3	31.7	30.1	30.7	30.5	31.1	31.5
12H	30.6	31.1	31.0	31.5	31.9	30.3	30.8	30.7	31.2	31.6
X=8H Y=4H	29.8	30.4	30.3	30.8	31.2	29.7	30.2	30.1	30.6	31.0
6H	30.5	31.0	31.0	31.4	31.9	30.3	30.8	30.8	31.2	31.7
8H	30.8	31.2	31.3	31.7	32.2	30.6	31.0	31.1	31.4	31.9
12H	31.1	31.5	31.6	31.9	32.4	30.9	31.2	31.4	31.7	32.2
X=12H Y=4H	29.9	30.4	30.3	30.8	31.2	29.7	30.2	30.1	30.6	31.0
6H	30.6	31.0	31.1	31.4	31.9	30.4	30.8	30.9	31.2	31.7
8H	30.9	31.3	31.4	31.8	32.3	30.7	31.1	31.2	31.5	32.0
Variations with the observer position at spacings:										
S=1.0H	+0.2/-0.3					+0.3/-0.4				
S=1.5H	+0.5/-0.7					+0.4/-0.7				
S=2.0H	+0.9/-1.1					+0.9/-1.2				

Calculate in accordance with CIE Pub.117. The table is revised with 2150lm ($8\log(F/F_0) = 2.7$).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	1100	51.1
	FL (0°-30°)	646	30.1
	FM (30°-60°)	352	16.4
	FH (60°-80°)	89	4.2
	FVH (80°-90°)	12	0.6
	BACK LIGHT	1051	48.9
	BL (0°-30°)	620	28.8
	BM (30°-60°)	335	15.6
	BH (60°-80°)	85	3.9
	BVH (80°-90°)	11	0.5
	UP LIGHT	0	0.0
	UL (90°-100°)	0	0.0
	UH (100°-180°)	0	0.0
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B2 U1 G1
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B2 U1 G1

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	4344.6	4.2	4.2	0.19	0.19
1.0-2.0	4311.8	12.4	16.5	0.58	0.77
2.0-3.0	4246.4	20.3	36.8	0.94	1.71
3.0-4.0	4149.3	27.8	64.6	1.29	3.01
4.0-5.0	4023.2	34.6	99.2	1.61	4.61
5.0-6.0	3870.8	40.7	139.9	1.89	6.51
6.0-7.0	3694.0	45.9	185.8	2.13	8.64
7.0-8.0	3494.9	50.0	235.8	2.33	10.97
8.0-9.0	3278.7	53.1	289.0	2.47	13.44
9.0-10.0	3051.0	55.2	344.2	2.57	16.00
10.0-11.0	2817.7	56.3	400.5	2.62	18.62
11.0-12.0	2586.9	56.6	457.0	2.63	21.25
12.0-13.0	2363.8	56.1	513.1	2.61	23.86
13.0-14.0	2152.4	55.1	568.2	2.56	26.42
14.0-15.0	1956.0	53.7	621.9	2.50	28.92
15.0-16.0	1776.2	52.1	674.0	2.42	31.34
16.0-17.0	1613.9	50.3	724.3	2.34	33.68
17.0-18.0	1470.8	48.5	772.8	2.26	35.93
18.0-19.0	1347.4	46.9	819.7	2.18	38.11
19.0-20.0	1242.3	45.5	865.1	2.11	40.23
20.0-21.0	1153.1	44.3	909.4	2.06	42.29
21.0-22.0	1076.2	43.3	952.7	2.01	44.30
22.0-23.0	1008.2	42.3	995.0	1.97	46.27
23.0-24.0	947.3	41.4	1036.4	1.93	48.19
24.0-25.0	891.6	40.5	1076.9	1.89	50.08
25.0-26.0	839.8	39.6	1116.6	1.84	51.92
26.0-27.0	791.6	38.7	1155.3	1.80	53.72
27.0-28.0	746.8	37.8	1193.1	1.76	55.48
28.0-29.0	704.8	36.9	1230.0	1.71	57.20
29.0-30.0	665.2	35.9	1265.9	1.67	58.87
30.0-31.0	628.4	35.0	1300.9	1.63	60.49
31.0-32.0	593.9	34.0	1334.9	1.58	62.08
32.0-33.0	560.7	33.0	1368.0	1.54	63.61
33.0-34.0	529.1	32.0	1400.0	1.49	65.10
34.0-35.0	499.8	31.0	1431.0	1.44	66.55
35.0-36.0	472.8	30.1	1461.2	1.40	67.95

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	447.3	29.2	1490.3	1.36	69.30
37.0-38.0	423.1	28.2	1518.6	1.31	70.62
38.0-39.0	400.4	27.3	1545.9	1.27	71.89
39.0-40.0	379.5	26.5	1572.4	1.23	73.12
40.0-41.0	360.1	25.6	1598.0	1.19	74.31
41.0-42.0	342.1	24.9	1622.9	1.16	75.47
42.0-43.0	324.8	24.1	1646.9	1.12	76.59
43.0-44.0	308.5	23.3	1670.2	1.08	77.67
44.0-45.0	293.5	22.6	1692.8	1.05	78.72
45.0-46.0	279.1	21.8	1714.6	1.02	79.73
46.0-47.0	265.5	21.1	1735.7	0.98	80.71
47.0-48.0	252.8	20.4	1756.2	0.95	81.66
48.0-49.0	240.7	19.8	1776.0	0.92	82.58
49.0-50.0	229.3	19.1	1795.1	0.89	83.47
50.0-51.0	218.3	18.5	1813.5	0.86	84.33
51.0-52.0	208.0	17.9	1831.4	0.83	85.16
52.0-53.0	198.1	17.2	1848.6	0.80	85.96
53.0-54.0	188.4	16.6	1865.2	0.77	86.74
54.0-55.0	179.3	16.0	1881.2	0.74	87.48
55.0-56.0	170.7	15.4	1896.7	0.72	88.20
56.0-57.0	162.6	14.9	1911.5	0.69	88.89
57.0-58.0	155.1	14.3	1925.9	0.67	89.56
58.0-59.0	148.4	13.9	1939.8	0.65	90.20
59.0-60.0	142.3	13.4	1953.2	0.63	90.83
60.0-61.0	136.4	13.0	1966.2	0.61	91.43
61.0-62.0	130.7	12.6	1978.8	0.59	92.02
62.0-63.0	125.1	12.2	1991.0	0.57	92.58
63.0-64.0	119.7	11.8	2002.7	0.55	93.13
64.0-65.0	114.6	11.3	2014.1	0.53	93.66
65.0-66.0	109.3	10.9	2025.0	0.51	94.16
66.0-67.0	103.8	10.4	2035.4	0.49	94.65
67.0-68.0	98.3	10.0	2045.4	0.46	95.11
68.0-69.0	93.0	9.5	2054.9	0.44	95.55
69.0-70.0	87.7	9.0	2063.9	0.42	95.97
70.0-71.0	82.5	8.5	2072.4	0.40	96.37
71.0-72.0	77.2	8.0	2080.4	0.37	96.74

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	4353.0	4353.0								
G1.0	4360.8	4311.6								
G2.0	4335.7	4239.2								
G3.0	4275.5	4135.0								
G4.0	4180.2	4006.6								
G5.0	4050.3	3855.6								
G6.0	3895.2	3681.9								
G7.0	3717.2	3481.9								
G8.0	3513.0	3267.6								
G9.0	3290.6	3043.6								
G10.0	3054.6	2815.1								
G11.0	2810.2	2590.8								
G12.0	2574.0	2372.7								
G13.0	2349.7	2159.0								
G14.0	2140.4	1960.4								
G15.0	1946.4	1776.9								
G16.0	1771.7	1609.9								
G17.0	1614.6	1459.5								
G18.0	1478.7	1330.2								
G19.0	1358.8	1222.0								
G20.0	1255.6	1132.7								
G21.0	1167.8	1056.4								
G22.0	1091.1	989.4								
G23.0	1022.2	930.3								
G24.0	960.8	876.2								
G25.0	905.0	824.3								
G26.0	853.4	776.4								
G27.0	804.8	731.9								
G28.0	759.3	691.4								
G29.0	716.5	652.1								
G30.0	676.8	615.4								
G31.0	639.3	582.1								
G32.0	605.7	548.5								
G33.0	572.2	516.5								
G34.0	539.8	488.0								
G35.0	509.0	462.4								
G36.0	482.1	437.5								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	456.6	413.2								
G38.0	431.6	391.0								
G39.0	408.8	370.1								
G40.0	388.0	351.0								
G41.0	368.0	333.6								
G42.0	350.0	316.6								
G43.0	331.8	300.9								
G44.0	314.8	286.6								
G45.0	299.7	272.8								
G46.0	284.4	259.7								
G47.0	270.3	247.6								
G48.0	257.2	236.0								
G49.0	245.2	224.5								
G50.0	233.8	213.8								
G51.0	222.7	203.1								
G52.0	212.4	193.8								
G53.0	201.9	184.2								
G54.0	192.5	174.9								
G55.0	183.3	166.4								
G56.0	174.5	158.6								
G57.0	166.1	151.3								
G58.0	158.6	144.6								
G59.0	151.8	138.7								
G60.0	145.6	133.2								
G61.0	139.3	127.6								
G62.0	133.3	122.4								
G63.0	127.9	116.8								
G64.0	122.7	111.6								
G65.0	117.7	106.3								
G66.0	112.2	100.9								
G67.0	106.6	95.5								
G68.0	101.0	90.2								
G69.0	95.5	85.1								
G70.0	90.1	80.0								
G71.0	84.7	75.1								
G72.0	79.4	69.8								
G73.0	74.2	64.9								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:

Unit: cd

[illegible]

Inspector: