中山雅大光电有限公司
www.artdon.cn
0760-22211886
0760-22211890

Report No.: Test Time: 2026-05-07 09:37

Luminaire Property

Luminaire Manufacturer:
Luminaire Description: 50D
Luminous Width (mm): -49
Current: 0.086 A
Power Factor: 0.495
Luminous Length (mm): -49
Voltage: 231.0 V
Power: 10.00 W


Photometric Results

CIE Class: Direct
Measurement Flux: 859.5 lm
Downward Ratio: 100%
Horizontal Diffuse Angle(50%): H54
Vertical Diffuse Angle(50%): V54
Luminaire Efficacy Rating (LER): 86.00
Max. Intensity: 1171.24 cd
S/MH(C0/C180): 0.89
Total Rated Lamp Lumens: 859.5 lm
Efficiency: 100%
Upward Ratio: 0%
Central Intensity: 1123.8 cd
Pos of Max. Intensity: H0 V9
S/MH(C90/C270): 0.89

Picture Of Luminaire





Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:
Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve






C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Isocandela (rectangle)




Imax (100%): 1171 cd

(10%): 117 cd	(16%): 187 cd
(25%): 293 cd	(40%): 468 cd
(63%): 738 cd	(100%): 1171 cd

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 11.4 lx

(1%): 0.1 lx	(2%): 0.2 lx
(5%): 0.6 lx	(10%): 1.1 lx
(20%): 2.3 lx	(50%): 5.7 lx
(100%): 11.4 lx	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Illuminance at a Distance




Dist(m)	Enadir(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
0.5	4495.20	0.51/0.51	0.2	1897.34
1.0	1123.80	1.01/1.02	0.8	474.34
1.5	499.47	1.52/1.53	1.8	210.82
2.0	280.95	2.02/2.04	3.3	118.58
2.5	179.81	2.53/2.55	5.1	75.89
3.0	124.87	3.03/3.06	7.3	52.70
4.0	70.24	4.04/4.08	13.0	29.65
5.0	44.95	5.05/5.10	20.4	18.97
15.0	4.99	15.15/15.29	183.5	2.11
20.0	2.81	20.20/20.39	326.2	1.19

Beam Angle(B): H53.6 V54.0 Field Angle(F): H74.8 V75.0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 1123.8 lx

(1%): 11.2 lx
(2%): 22.5 lx
(5%): 56.2 lx
(10%): 112.4 lx
(20%): 224.8 lx
(50%): 561.9 lx
(100%):1123.8 lx

C Plane (°):0.0-180.0: 180.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab:
Test Device: CHL-6E
Test Type: TYPE C
Distance: 3.010 m
Temperature:
Humidity:
Operator:
Inspector:

Area Flux Table

Unit: lm


Horizontal plane	Vertical plane																					
	-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
-90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.7	0.0
-40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	18.1	12.2
-30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	73.8	70.3
-20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	144.5	141.3
-10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	183.6	180.6
0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	186.0	183.0
10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	150.5	147.5
20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	79.2	75.8
30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	20.0	14.4
40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.8	0.0
50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	859	
Flux(T)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0
Flux(E)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	825	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

The Average Illuminance Effective Figure

Flux Out: 631.22lm



Height Avg./Nadir. E Beam Angle:53.6° Diameter / Area

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

UGR Table


Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	19.1	19.9	19.3	20.1	20.3	18.8	19.6	19.1	19.8	20.0
3H	18.9	19.6	19.2	19.9	20.1	18.7	19.4	19.0	19.6	19.9
4H	18.9	19.5	19.2	19.8	20.1	18.6	19.3	18.9	19.5	19.8
6H	18.8	19.4	19.1	19.7	20.0	18.5	19.1	18.9	19.4	19.7
8H	18.8	19.3	19.1	19.6	19.9	18.5	19.1	18.8	19.4	19.7
12H	18.7	19.3	19.1	19.6	19.9	18.5	19.0	18.8	19.3	19.6
X=4H Y=2H	18.9	19.5	19.2	19.8	20.1	18.6	19.3	18.9	19.5	19.8
3H	18.7	19.3	19.1	19.6	19.9	18.5	19.0	18.8	19.3	19.6
4H	18.6	19.1	19.0	19.5	19.8	18.4	18.9	18.8	19.2	19.6
6H	18.5	19.0	19.0	19.4	19.7	18.3	18.7	18.7	19.1	19.5
8H	18.5	18.9	18.9	19.3	19.7	18.2	18.7	18.7	19.0	19.4
12H	18.5	18.8	18.9	19.2	19.7	18.2	18.6	18.6	19.0	19.4
X=8H Y=4H	18.5	18.9	18.9	19.3	19.7	18.2	18.7	18.7	19.0	19.4
6H	18.4	18.7	18.9	19.2	19.6	18.2	18.5	18.6	18.9	19.4
8H	18.4	18.6	18.8	19.1	19.6	18.1	18.4	18.6	18.8	19.3
12H	18.3	18.6	18.8	19.0	19.5	18.1	18.3	18.5	18.8	19.3
X=12H Y=4H	18.5	18.8	18.9	19.2	19.7	18.2	18.6	18.6	19.0	19.4
6H	18.4	18.6	18.8	19.1	19.6	18.1	18.4	18.6	18.8	19.3
8H	18.3	18.6	18.8	19.0	19.5	18.1	18.3	18.5	18.8	19.3
Variations with the observer position at spacings:										
S=1.0H	+6.0/-31.9					+6.0/-34.2				
S=1.5H	+8.8/-36.2					+8.8/-39.7				
S=2.0H	+10.8/-1.$					+10.8/-1.$				

Calculate in accordance with CIE Pub.117. The table is revised with 859lm (8log(F/F0) = -0.5).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	438	50.9
FL (0°-30°)	363	42.3
FM (30°-60°)	74	8.7
FH (60°-80°)	0	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	422	49.1
BL (0°-30°)	352	40.9
BM (30°-60°)	70	8.2
BH (60°-80°)	0	0.0
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(**B**acklight,**U**plight,**G**lare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	1124.1	1.1	1.1	0.13	0.13
1.0-2.0	1125.5	3.2	4.3	0.38	0.50
2.0-3.0	1128.3	5.4	9.7	0.63	1.13
3.0-4.0	1132.0	7.6	17.3	0.88	2.01
4.0-5.0	1136.5	9.8	27.1	1.14	3.15
5.0-6.0	1141.0	12.0	39.1	1.40	4.54
6.0-7.0	1145.0	14.2	53.3	1.65	6.20
7.0-8.0	1148.1	16.4	69.7	1.91	8.11
8.0-9.0	1149.7	18.6	88.3	2.17	10.28
9.0-10.0	1149.0	20.8	109.1	2.42	12.70
10.0-11.0	1145.7	22.9	132.0	2.66	15.36
11.0-12.0	1139.3	24.9	156.9	2.90	18.26
12.0-13.0	1129.2	26.8	183.7	3.12	21.38
13.0-14.0	1115.2	28.5	212.3	3.32	24.70
14.0-15.0	1097.3	30.1	242.4	3.51	28.20
15.0-16.0	1075.2	31.5	273.9	3.67	31.87
16.0-17.0	1048.8	32.7	306.6	3.80	35.67
17.0-18.0	1018.1	33.6	340.2	3.91	39.58
18.0-19.0	983.0	34.2	374.4	3.98	43.56
19.0-20.0	943.7	34.5	408.9	4.02	47.58
20.0-21.0	900.7	34.6	443.5	4.02	51.60
21.0-22.0	854.7	34.4	477.9	4.00	55.60
22.0-23.0	806.2	33.8	511.7	3.94	59.53
23.0-24.0	756.1	33.1	544.8	3.85	63.38
24.0-25.0	705.2	32.1	576.8	3.73	67.11
25.0-26.0	653.5	30.9	607.7	3.59	70.70
26.0-27.0	601.6	29.4	637.1	3.42	74.13
27.0-28.0	549.4	27.8	664.9	3.24	77.36
28.0-29.0	496.8	26.0	690.9	3.02	80.39
29.0-30.0	444.5	24.0	714.9	2.79	83.18
30.0-31.0	393.0	21.9	736.8	2.54	85.73
31.0-32.0	343.0	19.7	756.4	2.29	88.01
32.0-33.0	295.3	17.4	773.8	2.02	90.04
33.0-34.0	250.8	15.2	789.0	1.77	91.80
34.0-35.0	209.9	13.0	802.1	1.52	93.32
35.0-36.0	173.3	11.0	813.1	1.28	94.60

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	141.5	9.2	822.3	1.07	95.68
37.0-38.0	114.9	7.7	830.0	0.89	96.57
38.0-39.0	92.9	6.3	836.3	0.74	97.31
39.0-40.0	74.7	5.2	841.5	0.61	97.91
40.0-41.0	59.8	4.3	845.8	0.50	98.41
41.0-42.0	47.6	3.5	849.3	0.40	98.81
42.0-43.0	37.3	2.8	852.0	0.32	99.13
43.0-44.0	28.9	2.2	854.2	0.25	99.39
44.0-45.0	21.9	1.7	855.9	0.20	99.58
45.0-46.0	16.1	1.3	857.2	0.15	99.73
46.0-47.0	11.2	0.9	858.0	0.10	99.83
47.0-48.0	7.3	0.6	858.6	0.07	99.90
48.0-49.0	4.3	0.4	859.0	0.04	99.94
49.0-50.0	2.2	0.2	859.2	0.02	99.97
50.0-51.0	1.0	0.1	859.3	0.01	99.97
51.0-52.0	0.5	0.0	859.3	0.00	99.98
52.0-53.0	0.3	0.0	859.3	0.00	99.98
53.0-54.0	0.3	0.0	859.3	0.00	99.99
54.0-55.0	0.3	0.0	859.4	0.00	99.99
55.0-56.0	0.1	0.0	859.4	0.00	99.99
56.0-57.0	0.1	0.0	859.4	0.00	99.99
57.0-58.0	0.1	0.0	859.4	0.00	99.99
58.0-59.0	0.1	0.0	859.4	0.00	99.99
59.0-60.0	0.1	0.0	859.4	0.00	99.99
60.0-61.0	0.1	0.0	859.4	0.00	99.99
61.0-62.0	0.1	0.0	859.4	0.00	100.00
62.0-63.0	0.2	0.0	859.5	0.00	100.00
63.0-64.0	0.1	0.0	859.5	0.00	100.00
64.0-65.0	0.0	0.0	859.5	0.00	100.00
65.0-66.0	0.0	0.0	859.5	0.00	100.00
66.0-67.0	0.0	0.0	859.5	0.00	100.00
67.0-68.0	0.0	0.0	859.5	0.00	100.00
68.0-69.0	0.0	0.0	859.5	0.00	100.00
69.0-70.0	0.0	0.0	859.5	0.00	100.00
70.0-71.0	0.0	0.0	859.5	0.00	100.00
71.0-72.0	0.0	0.0	859.5	0.00	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	0.0	0.0	859.5	0.00	100.00
73.0-74.0	0.0	0.0	859.5	0.00	100.00
74.0-75.0	0.0	0.0	859.5	0.00	100.00
75.0-76.0	0.0	0.0	859.5	0.00	100.00
76.0-77.0	0.0	0.0	859.5	0.00	100.00
77.0-78.0	0.0	0.0	859.5	0.00	100.00
78.0-79.0	0.0	0.0	859.5	0.00	100.00
79.0-80.0	0.0	0.0	859.5	0.00	100.00
80.0-81.0	0.0	0.0	859.5	0.00	100.00
81.0-82.0	0.0	0.0	859.5	0.00	100.00
82.0-83.0	0.0	0.0	859.5	0.00	100.00
83.0-84.0	0.0	0.0	859.5	0.00	100.00
84.0-85.0	0.0	0.0	859.5	0.00	100.00
85.0-86.0	0.0	0.0	859.5	0.00	100.00
86.0-87.0	0.0	0.0	859.5	0.00	100.00
87.0-88.0	0.0	0.0	859.5	0.00	100.00
88.0-89.0	0.0	0.0	859.5	0.00	100.00
89.0-90.0	0.0	0.0	859.5	0.00	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	1123.8	1123.8								
G1.0	1126.9	1121.7								
G2.0	1131.6	1121.7								
G3.0	1137.3	1122.6								
G4.0	1143.9	1124.3								
G5.0	1151.3	1126.5								
G6.0	1158.2	1128.2								
G7.0	1163.7	1129.8								
G8.0	1168.8	1130.1								
G9.0	1171.2	1128.6								
G10.0	1170.9	1125.2								
G11.0	1168.1	1118.7								
G12.0	1161.6	1108.9								
G13.0	1150.7	1095.4								
G14.0	1136.3	1078.3								
G15.0	1117.3	1057.3								
G16.0	1093.9	1032.4								
G17.0	1066.4	1002.6								
G18.0	1033.9	969.3								
G19.0	997.1	931.6								
G20.0	955.9	890.3								
G21.0	910.6	846.0								
G22.0	863.0	799.2								
G23.0	812.1	750.5								
G24.0	760.3	701.6								
G25.0	708.2	650.7								
G26.0	655.5	599.7								
G27.0	602.5	548.6								
G28.0	549.2	497.1								
G29.0	495.0	445.8								
G30.0	441.3	395.8								
G31.0	388.7	346.2								
G32.0	337.2	299.8								
G33.0	288.1	256.0								
G34.0	243.5	215.4								
G35.0	201.8	179.0								
G36.0	165.8	146.7								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	135.0	118.6								
G38.0	110.1	95.8								
G39.0	88.6	77.2								
G40.0	71.0	62.0								
G41.0	56.6	49.7								
G42.0	44.4	39.6								
G43.0	34.2	31.1								
G44.0	26.1	24.0								
G45.0	19.4	18.2								
G46.0	13.7	13.1								
G47.0	9.2	8.9								
G48.0	5.6	5.7								
G49.0	3.0	3.0								
G50.0	1.4	1.4								
G51.0	0.8	0.4								
G52.0	0.4	0.3								
G53.0	0.4	0.0								
G54.0	0.6	0.0								
G55.0	0.4	0.0								
G56.0	0.2	0.0								
G57.0	0.2	0.0								
G58.0	0.2	0.0								
G59.0	0.2	0.0								
G60.0	0.3	0.0								
G61.0	0.2	0.0								
G62.0	0.3	0.0								
G63.0	0.3	0.0								
G64.0	0.2	0.0								
G65.0	0.0	0.0								
G66.0	0.2	0.0								
G67.0	0.0	0.0								
G68.0	0.0	0.0								
G69.0	0.0	0.0								
G70.0	0.0	0.0								
G71.0	0.0	0.0								
G72.0	0.0	0.0								
G73.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table (Continue 2)

Unit: cd

G\C	C0.0	C180.0								
G74.0	0.0	0.0								
G75.0	0.0	0.0								
G76.0	0.0	0.0								
G77.0	0.0	0.0								
G78.0	0.0	0.0								
G79.0	0.0	0.0								
G80.0	0.0	0.0								
G81.0	0.0	0.0								
G82.0	0.0	0.0								
G83.0	0.0	0.0								
G84.0	0.0	0.0								
G85.0	0.0	0.0								
G86.0	0.0	0.0								
G87.0	0.0	0.0								
G88.0	0.0	0.0								
G89.0	0.0	0.0								
G90.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector: