

Report No.:

Test Time: 2026-09-10 16:58

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: 51.07533 24D

Luminous Width (mm): -67

Current: 0.147 A

Power Factor: 0.953

Luminous Length (mm): -67

Voltage: 228.5 V

Power: 32.20 W

Photometric Results

CIE Class: Direct

Measurement Flux: 3262.8 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H31.7

Vertical Diffuse Angle(50%): V31.7

Luminaire Efficacy Rating (LER): 101.38

Max. Intensity: 9965.59 cd

S/MH(C0/C180): 0.53

Total Rated Lamp Lumens: 3262.8 lm

Efficiency: 100%


Upward Ratio: 0%

Central Intensity: 9923.38 cd


Pos of Max. Intensity: H0 V1

S/MH(C90/C270): 0.53

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0



Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 9966 cd

(10%): 997 cd	(16%): 1594 cd
(25%): 2491 cd	(40%): 3986 cd
(63%): 6278 cd	(100%): 9966 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 99.6 lx

(1%): 1.0 lx	(2%): 2.0 lx
(5%): 5.0 lx	(10%): 10.0 lx
(20%): 19.9 lx	(50%): 49.8 lx
(100%): 99.6 lx	


C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 9923.4 lx


(1%): 99.2 lx	(2%): 198.5 lx
(5%): 496.2 lx	(10%): 992.3 lx
(20%): 1984.7 lx	(50%): 4961.7 lx
(100%): 9923.4 lx	

C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

The Average Illuminance Effective Figure



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	16.4	17.1	16.7	17.3	17.5	15.6	16.3	15.9	16.5	16.7
3H	16.3	16.9	16.6	17.1	17.4	15.5	16.1	15.8	16.4	16.6
4H	16.2	16.8	16.5	17.1	17.3	15.5	16.0	15.8	16.3	16.5
6H	16.2	16.7	16.5	17.0	17.2	15.4	15.9	15.7	16.2	16.5
8H	16.1	16.6	16.4	16.9	17.2	15.3	15.9	15.7	16.1	16.4
12H	16.1	16.6	16.4	16.9	17.2	15.3	15.8	15.6	16.1	16.4
X=4H Y=2H	16.3	16.8	16.6	17.1	17.3	15.5	16.1	15.8	16.3	16.6
3H	16.1	16.6	16.5	16.9	17.2	15.4	15.9	15.7	16.2	16.5
4H	16.0	16.5	16.4	16.8	17.2	15.3	15.7	15.7	16.1	16.4
6H	16.0	16.3	16.4	16.7	17.1	15.2	15.6	15.6	16.0	16.3
8H	15.9	16.3	16.3	16.7	17.1	15.1	15.5	15.6	15.9	16.3
12H	15.9	16.2	16.3	16.6	17.0	15.1	15.4	15.5	15.8	16.3
X=8H Y=4H	15.9	16.3	16.3	16.7	17.1	15.1	15.5	15.6	15.9	16.3
6H	15.8	16.1	16.3	16.5	17.0	15.0	15.3	15.5	15.8	16.2
8H	15.8	16.0	16.2	16.5	16.9	15.0	15.3	15.5	15.7	16.2
12H	15.7	15.9	16.2	16.4	16.9	15.0	15.2	15.4	15.6	16.1
X=12H Y=4H	15.9	16.2	16.3	16.6	17.0	15.1	15.4	15.5	15.8	16.3
6H	15.8	16.0	16.2	16.5	16.9	15.0	15.3	15.5	15.7	16.2
8H	15.7	15.9	16.2	16.4	16.9	15.0	15.2	15.4	15.6	16.1
Variations with the observer position at spacings:										
S=1.0H	+5.2/-6.5					+4.9/-6.5				
S=1.5H	+7.9/-8.9					+7.6/-8.6				
S=2.0H	+9.9/-14.3					+9.6/-17.0				

Calculate in accordance with CIE Pub.117. The table is revised with 3263lm ($8\log(F/F_0) = 4.1$).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	1728	53.0
	FL (0°-30°)	1586	48.6
	FM (30°-60°)	139	4.3
	FH (60°-80°)	3	0.1
	FVH (80°-90°)	0	0.0
	BACK LIGHT	1534	47.0
	BL (0°-30°)	1415	43.4
	BM (30°-60°)	116	3.6
	BH (60°-80°)	3	0.1
	BVH (80°-90°)	0	0.0
	UP LIGHT	0	0.0
	UL (90°-100°)	0	0.0
	UH (100°-180°)	0	0.0
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B3 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B3 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	9912.4	9.5	9.5	0.29	0.29
1.0-2.0	9866.8	28.3	37.8	0.87	1.16
2.0-3.0	9776.4	46.8	84.6	1.43	2.59
3.0-4.0	9645.6	64.6	149.1	1.98	4.57
4.0-5.0	9471.5	81.5	230.6	2.50	7.07
5.0-6.0	9251.7	97.2	327.9	2.98	10.05
6.0-7.0	8987.1	111.6	439.4	3.42	13.47
7.0-8.0	8679.6	124.2	563.7	3.81	17.28
8.0-9.0	8332.4	135.1	698.7	4.14	21.42
9.0-10.0	7948.4	143.9	842.6	4.41	25.82
10.0-11.0	7531.1	150.5	993.1	4.61	30.44
11.0-12.0	7086.7	154.9	1148.0	4.75	35.19
12.0-13.0	6621.6	157.2	1305.2	4.82	40.00
13.0-14.0	6140.3	157.2	1462.4	4.82	44.82
14.0-15.0	5648.0	155.1	1617.5	4.75	49.57
15.0-16.0	5152.4	151.0	1768.5	4.63	54.20
16.0-17.0	4660.9	145.2	1913.6	4.45	58.65
17.0-18.0	4181.1	137.9	2051.5	4.23	62.88
18.0-19.0	3719.0	129.4	2180.9	3.97	66.84
19.0-20.0	3279.9	120.1	2301.0	3.68	70.52
20.0-21.0	2869.8	110.2	2411.2	3.38	73.90
21.0-22.0	2491.4	100.1	2511.3	3.07	76.97
22.0-23.0	2148.0	90.1	2601.5	2.76	79.73
23.0-24.0	1842.0	80.5	2682.0	2.47	82.20
24.0-25.0	1571.0	71.4	2753.4	2.19	84.39
25.0-26.0	1336.2	63.1	2816.5	1.93	86.32
26.0-27.0	1135.3	55.5	2872.1	1.70	88.03
27.0-28.0	964.5	48.8	2920.9	1.50	89.52
28.0-29.0	818.7	42.8	2963.8	1.31	90.84
29.0-30.0	692.8	37.4	3001.2	1.15	91.98
30.0-31.0	586.1	32.6	3033.8	1.00	92.98
31.0-32.0	493.8	28.3	3062.1	0.87	93.85
32.0-33.0	414.6	24.4	3086.5	0.75	94.60
33.0-34.0	346.0	20.9	3107.4	0.64	95.24
34.0-35.0	286.1	17.8	3125.2	0.54	95.78
35.0-36.0	235.9	15.0	3140.2	0.46	96.24

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	196.4	12.8	3153.0	0.39	96.64
37.0-38.0	167.0	11.1	3164.2	0.34	96.98
38.0-39.0	142.5	9.7	3173.9	0.30	97.28
39.0-40.0	122.9	8.6	3182.5	0.26	97.54
40.0-41.0	108.2	7.7	3190.2	0.24	97.78
41.0-42.0	96.1	7.0	3197.2	0.21	97.99
42.0-43.0	86.3	6.4	3203.6	0.20	98.19
43.0-44.0	76.9	5.8	3209.4	0.18	98.36
44.0-45.0	70.1	5.4	3214.8	0.17	98.53
45.0-46.0	63.3	5.0	3219.7	0.15	98.68
46.0-47.0	56.9	4.5	3224.2	0.14	98.82
47.0-48.0	52.8	4.3	3228.5	0.13	98.95
48.0-49.0	47.5	3.9	3232.4	0.12	99.07
49.0-50.0	43.3	3.6	3236.0	0.11	99.18
50.0-51.0	39.6	3.3	3239.4	0.10	99.28
51.0-52.0	34.3	2.9	3242.3	0.09	99.37
52.0-53.0	30.2	2.6	3244.9	0.08	99.45
53.0-54.0	27.1	2.4	3247.3	0.07	99.53
54.0-55.0	23.0	2.1	3249.4	0.06	99.59
55.0-56.0	20.0	1.8	3251.2	0.06	99.65
56.0-57.0	18.1	1.7	3252.8	0.05	99.70
57.0-58.0	15.8	1.5	3254.3	0.04	99.74
58.0-59.0	14.3	1.3	3255.6	0.04	99.78
59.0-60.0	12.4	1.2	3256.8	0.04	99.82
60.0-61.0	10.9	1.0	3257.9	0.03	99.85
61.0-62.0	10.9	1.1	3258.9	0.03	99.88
62.0-63.0	10.2	1.0	3259.9	0.03	99.91
63.0-64.0	9.0	0.9	3260.8	0.03	99.94
64.0-65.0	7.5	0.7	3261.5	0.02	99.96
65.0-66.0	4.5	0.5	3262.0	0.01	99.98
66.0-67.0	2.6	0.3	3262.3	0.01	99.98
67.0-68.0	2.3	0.2	3262.5	0.01	99.99
68.0-69.0	1.9	0.2	3262.7	0.01	100.00
69.0-70.0	0.8	0.1	3262.8	0.00	100.00
70.0-71.0	0.0	0.0	3262.8	0.00	100.00
71.0-72.0	0.0	0.0	3262.8	0.00	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	9923.4	9923.4								
G1.0	9965.6	9837.4								
G2.0	9962.6	9701.8								
G3.0	9915.8	9525.4								
G4.0	9829.9	9311.3								
G5.0	9691.2	9053.5								
G6.0	9510.3	8751.9								
G7.0	9282.6	8403.7								
G8.0	9006.7	8025.2								
G9.0	8687.1	7610.6								
G10.0	8325.3	7170.4								
G11.0	7916.7	6712.1								
G12.0	7482.5	6235.7								
G13.0	7024.2	5744.2								
G14.0	6541.7	5251.2								
G15.0	6042.7	4756.6								
G16.0	5534.6	4275.7								
G17.0	5022.0	3811.4								
G18.0	4524.5	3366.6								
G19.0	4042.0	2942.9								
G20.0	3579.2	2555.5								
G21.0	3140.4	2204.2								
G22.0	2734.9	1886.1								
G23.0	2359.5	1611.7								
G24.0	2026.3	1370.5								
G25.0	1726.3	1160.9								
G26.0	1471.5	986.0								
G27.0	1243.8	839.8								
G28.0	1058.4	716.1								
G29.0	892.5	607.6								
G30.0	759.9	511.1								
G31.0	651.3	422.1								
G32.0	553.3	348.3								
G33.0	467.4	289.5								
G34.0	386.0	241.2								
G35.0	313.6	203.5								
G36.0	256.3	170.4								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	212.6	146.2								
G38.0	180.9	128.1								
G39.0	150.8	110.1								
G40.0	131.2	99.5								
G41.0	113.1	88.9								
G42.0	101.0	81.4								
G43.0	88.9	73.9								
G44.0	78.4	66.3								
G45.0	73.9	61.8								
G46.0	63.3	54.3								
G47.0	60.3	49.8								
G48.0	55.8	45.2								
G49.0	48.2	40.7								
G50.0	48.2	36.2								
G51.0	42.2	31.7								
G52.0	36.2	27.1								
G53.0	34.7	22.6								
G54.0	30.1	21.1								
G55.0	24.1	16.6								
G56.0	22.6	16.6								
G57.0	18.1	15.1								
G58.0	16.6	13.6								
G59.0	15.1	12.1								
G60.0	12.1	10.6								
G61.0	12.1	9.1								
G62.0	12.1	10.6								
G63.0	10.6	7.5								
G64.0	10.6	7.5								
G65.0	7.5	4.5								
G66.0	4.5	1.5								
G67.0	4.5	0.0								
G68.0	4.5	0.0								
G69.0	3.0	0.0								
G70.0	0.0	0.0								
G71.0	0.0	0.0								
G72.0	0.0	0.0								
G73.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 3.010 m

Humidity:

Inspector:

Unit: cd

Inspector: