Report No.: Test Time: 2026-09-10 15:25

Luminaire Property


Luminaire Manufacturer:
Luminaire Description: 36D
Luminous Width (mm): -40
Current: 0.064 A
Power Factor: 0.941
Luminous Length (mm): -40
Voltage: 228.7 V
Power: 13.80 W

Photometric Results

CIE Class: Direct
Measurement Flux: 1088 lm
Downward Ratio: 100%
Horizontal Diffuse Angle(50%): H39.2
Vertical Diffuse Angle(50%): V39.2
Luminaire Efficacy Rating (LER): 78.89
Max. Intensity: 2357.06 cd
S/MH(C0/C180): 0.64
Total Rated Lamp Lumens: 1088.0 lm
Efficiency: 100%
Upward Ratio: 0%
Central Intensity: 2342.48 cd
Pos of Max. Intensity: H0 V2
S/MH(C90/C270): 0.64


Picture Of Luminaire


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:
Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve






C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Isocandela (rectangle)




Imax (100%): 2357 cd

(10%): 236 cd
(16%): 377 cd
(25%): 589 cd
(40%): 943 cd
(63%): 1485 cd
(100%): 2357 cd

C Plane (°):0.0-180.0: 180.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab:
Test Device: CHL-6E
Test Type: TYPE C
Distance: 3.010 m
Temperature:
Humidity:
Operator:
Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 23.5 lx

(1%): 0.2 lx
(2%): 0.5 lx
(5%): 1.2 lx
(10%): 2.4 lx
(20%): 4.7 lx
(50%): 11.8 lx
(100%): 23.5 lx

C Plane (°):0.0-180.0: 180.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab:
Test Device: CHL-6E
Test Type: TYPE C
Distance: 3.010 m
Temperature:
Humidity:
Operator:
Inspector:

Illuminance at a Distance




Dist(m)	Enadir(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
0.5	9369.92	0.36/0.36	0.1	4252.90
1.0	2342.48	0.71/0.71	0.4	1063.23
1.5	1041.10	1.07/1.07	0.9	472.54
2.0	585.62	1.42/1.43	1.6	265.81
2.5	374.80	1.78/1.78	2.5	170.12
3.0	260.28	2.13/2.14	3.6	118.14
4.0	146.40	2.84/2.86	6.4	66.45
5.0	93.70	3.56/3.57	10.0	42.53
15.0	10.41	10.67/10.71	89.7	4.73
20.0	5.86	14.22/14.28	159.5	2.66

Beam Angle(B): H39.1 V39.3 Field Angle(F): H64.8 V64.9

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 2342.5 lx

(1%): 23.4 lx
(2%): 46.8 lx
(5%): 117.1 lx
(10%): 234.2 lx
(20%): 468.5 lx
(50%):1171.2 lx
(100%):2342.5 lx

C Plane (°):0.0-180.0: 180.0
Gamma Plane (°):0.0-90.0:1.0
Test Lab:
Test Device: CHL-6E
Test Type: TYPE C
Distance: 3.010 m
Temperature:
Humidity:
Operator:
Inspector:

Area Flux Table

Unit: lm


Horizontal plane	Vertical plane																							
	-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
-90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.5	0.0
-50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.6	0.6	0.4	0.2	0.1	0.0	0.0	0.0	0.0	0.0	2.9	0.0
-40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.4	2.9	4.2	4.2	2.9	1.3	0.4	0.1	0.0	0.0	0.0	18.0	2.8
-30	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.3	1.4	5.0	11.3	17.5	17.5	11.3	5.0	1.4	0.3	0.1	0.0	71.1	59.4
-20	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.6	3.4	12.0	29.7	44.1	44.1	29.7	12.0	3.4	0.6	0.2	0.1	180.0	170.4
-10	0.0	0.0	0.0	0.0	0.0	0.2	0.2	0.9	5.0	19.3	45.5	63.3	63.3	45.5	19.3	5.0	0.9	0.2	0.1	268.5	259.3
0	0.0	0.0	0.0	0.0	0.0	0.2	0.2	0.9	5.0	19.4	45.5	64.2	64.2	45.5	19.4	5.0	0.9	0.2	0.1	270.4	261.2
10	0.0	0.0	0.0	0.0	0.0	0.2	0.2	0.6	3.4	12.1	30.0	44.2	44.2	30.0	12.1	3.4	0.6	0.2	0.1	181.1	171.4
20	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.4	1.5	4.9	11.5	18.1	18.1	11.5	4.9	1.5	0.4	0.1	0.0	72.9	61.2
30	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.2	0.5	1.3	2.9	4.1	4.1	2.9	1.3	0.5	0.2	0.1	0.0	18.1	2.7
40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.2	0.3	0.5	0.7	0.7	0.5	0.3	0.2	0.1	0.0	0.0	3.4	0.0
50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.7	0.0
60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.0
70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90																				1088	
Flux(T)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0
Flux(E)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	989

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

The Average Illuminance Effective Figure

Flux Out: 626.07lm



Height | Avg./Nadir. E | Beam Angle:39.1° | Diameter / Area

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

UGR Table


Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	18.4	19.1	18.6	19.3	19.5	18.4	19.1	18.6	19.3	19.5
3H	18.2	18.9	18.5	19.1	19.4	18.2	18.9	18.5	19.1	19.4
4H	18.2	18.8	18.5	19.0	19.3	18.2	18.8	18.5	19.0	19.3
6H	18.1	18.7	18.4	18.9	19.2	18.1	18.7	18.4	18.9	19.2
8H	18.0	18.6	18.4	18.9	19.2	18.0	18.6	18.4	18.9	19.2
12H	18.0	18.5	18.4	18.8	19.2	18.0	18.5	18.4	18.8	19.2
X=4H Y=2H	18.2	18.8	18.5	19.0	19.3	18.2	18.8	18.5	19.0	19.3
3H	18.0	18.6	18.4	18.9	19.2	18.0	18.5	18.4	18.8	19.2
4H	17.9	18.4	18.3	18.7	19.1	17.9	18.4	18.3	18.7	19.1
6H	17.9	18.3	18.3	18.6	19.0	17.8	18.3	18.2	18.6	19.0
8H	17.8	18.2	18.2	18.6	19.0	17.8	18.2	18.2	18.6	19.0
12H	17.8	18.1	18.2	18.5	18.9	17.8	18.1	18.2	18.5	18.9
X=8H Y=4H	17.8	18.2	18.2	18.6	19.0	17.8	18.2	18.2	18.6	19.0
6H	17.7	18.0	18.2	18.4	18.9	17.7	18.0	18.2	18.4	18.9
8H	17.7	17.9	18.1	18.4	18.9	17.7	17.9	18.1	18.4	18.8
12H	17.6	17.9	18.1	18.3	18.8	17.6	17.8	18.1	18.3	18.8
X=12H Y=4H	17.8	18.1	18.2	18.5	18.9	17.8	18.1	18.2	18.5	18.9
6H	17.7	17.9	18.1	18.4	18.9	17.7	17.9	18.1	18.4	18.8
8H	17.6	17.9	18.1	18.3	18.8	17.6	17.8	18.1	18.3	18.8
Variations with the observer position at spacings:										
S=1.0H	+5.3/-10.6					+5.3/-11.5				
S=1.5H	+8.0/-15.8					+8.1/-17.5				
S=2.0H	+10.0/-30.8					+10.1/-33.2				

Calculate in accordance with CIE Pub.117. The table is revised with 1088lm (8log(F/F0) = 0.3).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	547	50.3
FL (0°-30°)	478	43.9
FM (30°-60°)	68	6.3
FH (60°-80°)	1	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	541	49.7
BL (0°-30°)	473	43.5
BM (30°-60°)	68	6.2
BH (60°-80°)	0	0.0
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(**B**acklight,**U**plight,**G**lare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	2340.9	2.2	2.2	0.21	0.21
1.0-2.0	2333.6	6.7	8.9	0.62	0.82
2.0-3.0	2318.6	11.1	20.0	1.02	1.84
3.0-4.0	2295.7	15.4	35.4	1.41	3.25
4.0-5.0	2264.3	19.5	54.9	1.79	5.04
5.0-6.0	2225.4	23.4	78.3	2.15	7.19
6.0-7.0	2181.5	27.1	105.4	2.49	9.68
7.0-8.0	2133.1	30.5	135.9	2.81	12.49
8.0-9.0	2079.0	33.7	169.6	3.10	15.59
9.0-10.0	2019.5	36.6	206.1	3.36	18.95
10.0-11.0	1955.5	39.1	245.2	3.59	22.54
11.0-12.0	1886.8	41.3	286.5	3.79	26.33
12.0-13.0	1813.4	43.0	329.5	3.96	30.28
13.0-14.0	1734.8	44.4	373.9	4.08	34.37
14.0-15.0	1651.3	45.3	419.3	4.17	38.53
15.0-16.0	1563.9	45.8	465.1	4.21	42.75
16.0-17.0	1472.5	45.9	510.9	4.21	46.96
17.0-18.0	1379.0	45.5	556.4	4.18	51.14
18.0-19.0	1283.3	44.7	601.1	4.10	55.24
19.0-20.0	1185.3	43.4	644.5	3.99	59.23
20.0-21.0	1086.4	41.7	686.2	3.83	63.07
21.0-22.0	988.5	39.7	725.9	3.65	66.72
22.0-23.0	892.5	37.5	763.4	3.44	70.16
23.0-24.0	798.7	34.9	798.3	3.21	73.37
24.0-25.0	708.4	32.2	830.5	2.96	76.33
25.0-26.0	623.5	29.4	859.9	2.71	79.04
26.0-27.0	545.2	26.7	886.6	2.45	81.49
27.0-28.0	474.4	24.0	910.6	2.21	83.70
28.0-29.0	412.0	21.6	932.2	1.98	85.68
29.0-30.0	357.4	19.3	951.5	1.77	87.45
30.0-31.0	309.4	17.2	968.7	1.58	89.03
31.0-32.0	267.5	15.3	984.0	1.41	90.44
32.0-33.0	231.9	13.7	997.7	1.26	91.70
33.0-34.0	202.1	12.2	1009.9	1.12	92.82
34.0-35.0	176.2	10.9	1020.9	1.01	93.83
35.0-36.0	153.1	9.7	1030.6	0.90	94.72

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	132.5	8.6	1039.3	0.79	95.52
37.0-38.0	113.2	7.6	1046.8	0.69	96.21
38.0-39.0	95.0	6.5	1053.3	0.60	96.81
39.0-40.0	78.3	5.5	1058.8	0.50	97.31
40.0-41.0	63.8	4.5	1063.3	0.42	97.73
41.0-42.0	51.5	3.7	1067.1	0.34	98.07
42.0-43.0	41.5	3.1	1070.1	0.28	98.36
43.0-44.0	33.6	2.5	1072.7	0.23	98.59
44.0-45.0	27.6	2.1	1074.8	0.19	98.78
45.0-46.0	23.0	1.8	1076.6	0.17	98.95
46.0-47.0	19.5	1.5	1078.1	0.14	99.09
47.0-48.0	16.8	1.4	1079.5	0.12	99.22
48.0-49.0	14.5	1.2	1080.7	0.11	99.33
49.0-50.0	12.6	1.0	1081.7	0.10	99.42
50.0-51.0	10.9	0.9	1082.7	0.08	99.51
51.0-52.0	9.4	0.8	1083.5	0.07	99.58
52.0-53.0	8.1	0.7	1084.2	0.06	99.65
53.0-54.0	6.9	0.6	1084.8	0.06	99.70
54.0-55.0	6.0	0.5	1085.3	0.05	99.75
55.0-56.0	5.4	0.5	1085.8	0.04	99.80
56.0-57.0	4.6	0.4	1086.2	0.04	99.83
57.0-58.0	4.0	0.4	1086.6	0.03	99.87
58.0-59.0	3.5	0.3	1086.9	0.03	99.90
59.0-60.0	2.9	0.3	1087.2	0.03	99.92
60.0-61.0	2.4	0.2	1087.4	0.02	99.94
61.0-62.0	2.0	0.2	1087.6	0.02	99.96
62.0-63.0	1.6	0.2	1087.8	0.01	99.98
63.0-64.0	1.1	0.1	1087.9	0.01	99.99
64.0-65.0	0.7	0.1	1088.0	0.01	99.99
65.0-66.0	0.4	0.0	1088.0	0.00	100.00
66.0-67.0	0.2	0.0	1088.0	0.00	100.00
67.0-68.0	0.1	0.0	1088.0	0.00	100.00
68.0-69.0	0.1	0.0	1088.0	0.00	100.00
69.0-70.0	0.0	0.0	1088.0	0.00	100.00
70.0-71.0	0.0	0.0	1088.0	0.00	100.00
71.0-72.0	0.0	0.0	1088.0	0.00	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	0.0	0.0	1088.0	0.00	100.00
73.0-74.0	0.0	0.0	1088.0	0.00	100.00
74.0-75.0	0.0	0.0	1088.0	0.00	100.00
75.0-76.0	0.0	0.0	1088.0	0.00	100.00
76.0-77.0	0.0	0.0	1088.0	0.00	100.00
77.0-78.0	0.0	0.0	1088.0	0.00	100.00
78.0-79.0	0.0	0.0	1088.0	0.00	100.00
79.0-80.0	0.0	0.0	1088.0	0.00	100.00
80.0-81.0	0.0	0.0	1088.0	0.00	100.00
81.0-82.0	0.0	0.0	1088.0	0.00	100.00
82.0-83.0	0.0	0.0	1088.0	0.00	100.00
83.0-84.0	0.0	0.0	1088.0	0.00	100.00
84.0-85.0	0.0	0.0	1088.0	0.00	100.00
85.0-86.0	0.0	0.0	1088.0	0.00	100.00
86.0-87.0	0.0	0.0	1088.0	0.00	100.00
87.0-88.0	0.0	0.0	1088.0	0.00	100.00
88.0-89.0	0.0	0.0	1088.0	0.00	100.00
89.0-90.0	0.0	0.0	1088.0	0.00	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	2342.5	2342.5								
G1.0	2355.7	2322.8								
G2.0	2357.1	2298.6								
G3.0	2349.1	2269.7								
G4.0	2326.7	2237.2								
G5.0	2291.9	2201.4								
G6.0	2248.2	2160.2								
G7.0	2197.4	2120.0								
G8.0	2140.4	2074.8								
G9.0	2074.5	2026.4								
G10.0	2004.8	1972.2								
G11.0	1931.8	1913.2								
G12.0	1853.0	1849.3								
G13.0	1774.9	1776.5								
G14.0	1691.2	1696.4								
G15.0	1605.8	1611.8								
G16.0	1516.1	1521.8								
G17.0	1423.9	1428.0								
G18.0	1332.3	1331.7								
G19.0	1239.1	1229.9								
G20.0	1145.4	1126.7								
G21.0	1050.4	1023.0								
G22.0	956.4	924.1								
G23.0	862.0	827.6								
G24.0	770.1	735.1								
G25.0	682.8	645.8								
G26.0	598.8	566.5								
G27.0	520.1	495.6								
G28.0	449.7	432.3								
G29.0	389.2	376.9								
G30.0	335.1	328.7								
G31.0	287.8	285.9								
G32.0	246.7	249.8								
G33.0	211.6	219.6								
G34.0	182.7	194.3								
G35.0	158.9	169.1								
G36.0	139.3	145.2								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	121.5	123.9								
G38.0	104.1	103.6								
G39.0	87.2	85.0								
G40.0	72.1	69.1								
G41.0	59.0	55.3								
G42.0	48.2	43.7								
G43.0	39.3	34.7								
G44.0	32.4	27.9								
G45.0	26.7	23.1								
G46.0	22.7	19.4								
G47.0	19.4	16.5								
G48.0	17.0	14.3								
G49.0	14.7	12.2								
G50.0	13.1	10.4								
G51.0	11.6	8.6								
G52.0	10.4	7.2								
G53.0	8.9	6.0								
G54.0	7.5	5.1								
G55.0	6.8	4.8								
G56.0	6.0	3.9								
G57.0	5.1	3.5								
G58.0	4.8	2.7								
G59.0	3.9	2.4								
G60.0	3.5	2.0								
G61.0	2.8	1.5								
G62.0	2.4	1.2								
G63.0	2.0	0.8								
G64.0	1.5	0.2								
G65.0	1.0	0.0								
G66.0	0.4	0.0								
G67.0	0.4	0.0								
G68.0	0.2	0.0								
G69.0	0.2	0.0								
G70.0	0.0	0.0								
G71.0	0.0	0.0								
G72.0	0.0	0.0								
G73.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector:

Candlepower Table (Continue 2)

Unit: cd

G\C	C0.0	C180.0								
G74.0	0.0	0.0								
G75.0	0.0	0.0								
G76.0	0.0	0.0								
G77.0	0.0	0.0								
G78.0	0.0	0.0								
G79.0	0.0	0.0								
G80.0	0.0	0.0								
G81.0	0.0	0.0								
G82.0	0.0	0.0								
G83.0	0.0	0.0								
G84.0	0.0	0.0								
G85.0	0.0	0.0								
G86.0	0.0	0.0								
G87.0	0.0	0.0								
G88.0	0.0	0.0								
G89.0	0.0	0.0								
G90.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 3.010 m
Humidity:
Inspector: